

Lecture

“Foundations of Language Science and Technology: Statistical Natural Language Processing”

Prof. Dr. D. Klakow

Exercise session: 19/12/2007

Exercise

“*Spam, Spam, Spam!*” Unsolicited email is commonly referred to as “spam”. Your task for this exercise session is to build a Naïve Bayes classifier that can automatically classify a given document (e.g. incoming email) using the two classes SPAM and HAM(=not spam).

Subtasks:

1. Download the data from

<http://www.coli.uni-saarland.de/courses/FLST/2007>

The package `flst_snlp.tgz` contains training and testing data for both spam and non-spam messages.

You can decompress the package with:

```
tar -zxvf flst_snlp.tgz
```

2. Build a word-based language model for each of the classes, HAM and SPAM. The training data are in the files `ham_training` and `spam_training`, respectively. Instead of using relative frequencies as your probabilities, smooth your language models with *absolute discounting*. Use the following equation:

$$P_{\delta}(x_i|\omega_k) = \frac{\max(N(x_i,\omega_k)-\delta,0)}{\sum_{x_i} N(x_i,\omega_k)} + \frac{\delta \cdot n_+}{\sum_{x_i} N(x_i,\omega_k)} \cdot \frac{1}{|V|}$$

where $n_+ = \sum_{x_i: N(x_i,\omega_k) > 0} 1$. It would be nice if the discounting parameter δ could be optionally specified as a command line option. Use $\delta = 0.7$ as a default value. The file `vocab_100000.wl` contains the vocabulary with which you are to build your language models.

3. Write a classifier that classifies each mail contained in the test file `ham_spam_testing`. A new mail begins with `####` followed by the class label. Your program should output the predicted class for each mail in the test file along with the overall number of correctly and incorrectly classified mails. The predicted class for the test mail is the class which has the highest probability according the class-specific language model and the class prior. In order to prevent an underflow in your classifier use a sum of logarithms instead of a product of the probabilities:

$$\hat{\omega} \propto \arg \max_{\omega_k} \log P_{\delta}(x|\omega_k) + \log P(\omega_k)$$

where $P_{\delta}(x|\omega_k)$ is a class-specific language model and $P(\omega_k)$ is a class prior.

General Remarks:

- You may implement this exercise in any programming language. However, we recommend either of the following languages: *Perl*, *Python* or *Ruby*.
- Please document your code properly, so that it can be easily tested without reading the entire source code.
- The exercise will be discussed in the exercise session on 19/12/2007. If you have not completed this task by then, we can discuss your questions/problems during this session.
- The **deadline** for this exercise is 21/12/2007.
- Send your program to `Michael.Wiegand@lsv.uni-saarland.de`
- In case you have further questions with regard to this exercise, please send your mail to the address mentioned above.